




THE PRODUCT RANGE OF BRUGG PIPES






PREMANT

Operating Temp. 250 °F
 Operating Pressure 362 psi
 DN 20-1000
 EN 253 Pre-Insulated Pipe
 Leak Detection




FLEXWELL FHK

Operating Temp. 302 °F
 Operating Pressure 362 psi
 DN 25-150
 1" to 6"
 Leak Detection





CASAFLEX

Operating Temp. 302 °F
 Operating Pressure 362 psi
 DN 20-100
 3/4" to 4"
 Leak Detection





CALPEX PUR-KING

Operating Temp. 176 °F
 (short term 203 °F)
 Operating Pressure 87 psi
 0.75" to 5.5"
 Up to 2" NSF61 certified





ARMOPEX

Operating Temp. 203 °F
 (short term 239 °F)
 Operating Pressure 174 psi
 DN 20-125
 1.25" to 5"

POLARFLEX

Operating Temp. from -40 to 140 °F
 Operating Pressure 100-200 psi
 DN 20-100
 1" to 4"
 Heat Trace Channel

CITIFLEX





Operating Temp. from -40 to 140 °F
 Operating Pressure 362 psi
 1" and 2"
 AWWA certified
 Heat Trace Channel






COOLFLEX

Operating Temp. from -40 to 140 °F
 Operating Pressure 100-200 psi
 DN 20-125
 1" to 4"


bruggpipes.com

BRUGG
 Pipes

Pioneers in Infrastructure



- Domestic production of our insulated PEX and PE pipes
- Continuous, custom coil lengths up to 3100ft (depending on OD)
- Domestic inventory of finished products and accessories

Additional advantages



- Thermal conductivity 0.1338 BTU·in/hr·ft²·°F (ASTM C158)
- Closed-cell structure 99%
- Long-lasting stability



- Small bending radii
- Bypass obstacles with ease
- No expansion elements



- Reliable connection technology
- Ingenious post-insulation technique
- Short delivery times



- No tools required
- Leak tightness tested to 4.4 psi
- Entry angle up to 20°



- We manufacture our products in line with EN 15632-1/-2
- Certified to ISO 9001 since 1985